

19" DYNAframe

High Density Open Frame System Racks
Single Frames d:80 mm Frame Unit



Width: 530 mm
Depth: 380 mm

Load Capacity: 600 kg.

U Height: 27U, 36U, 42U, 45U, 48U

Standards and Compliances:



ISO 9001
Quality Management System
EN 61587-1
Mechanical Structures for
Electronic Equipment
EN IEC 60297, 19" Mounting
EN IEC 60917 Overall Cabinet
Dimensions
EIA/ ECA-310 (D/E) 19" 482,6 mm
and U 44,45 mm Height Sizing



CE conform to
EN 60950-1
Information Technology
Equipment, Safety,
Part-1: General Requirement
EN IEC 62368-1 Audio/Video, Information
and Communication Technology
Equipment
Part 1: Safety requirements



UL listed to
UL 2416, Outline of Investigation for
Audio/Video, Information and
Communication Technology Equipment
Cabinet, Enclosure and Rack
Systems; UL 60950-1 and CSA C22.2
NO. 60950-1-07, Information Technology
Equipment Safety
Part 1: General Requirements
Environment Friendly;



ISO 14001 Environmental
Management System
RoHS compliancy
100% Recyclable Material

Standard Color:



RAL 7035 Light Grey



RAL 9005 Black



DYNAframe Series Open Frame System Racks Networking Frames are with 19" w:530 mm and d:380 mm base L parts size, physical sizes, 5 different heights, gives a wide selection for users.

Single frame depth is mentioned as the depth of base frame, the depth of frame unit is 80 mm.

19" DYNAframe


High Density Open Frame System Racks

Single Frames d:80 mm Frame Unit


Construction Drawings

Width: 530 mm


Depth: 380 mm




Bottom view




Isometric view




Front view




Side view




Rear view




Dimensions in width and height



Top view



Exploded view



Top view mounting dimensions

19" DYNAframe Open Frame System Racks Single Frames d=80 mm Frame Unit W=530 mm D=380 mm

Product Number*	Product Description	Size WxDxH mm	h Size in U	h in mm	H mm, overall without feet and/or castor	Width Overall mm	Width Rail to Rail	Depth Overall mm	Depth of Rail	PACKING DIMENSIONS WxDxH mm	QTY IN PALLET	Standard NET Weight of Product kgs	Gross Weight of Product kgs
LN-OF27USD380-CC27U D=80 mm	Frame Single Frame Open System Rack D=380 mm LN-OF36USD380-CC36U D=80 mm	530x380x1356	27U	1200	1356	530	19"	380	80	165x120x1375	1	20	21
Frame Single Frame Open System Rack D=380 mm LN-OF42USD380-CC42U D=80 mm		530x380x1756	36U	1600	1756	530	19"	380	80	165x120x1775	1	22,5	23,5
Frame Single Frame Open System Rack D=380 mm LN-OF45USD380-CC45U D=80 mm	Frame Single Frame Open System Rack D=380 mm LN-OF48USD380-CC48U D=80 mm	530x380x2022	42U	1867	2022	530	19"	380	80	165x120x2040	1	23,5	24
Open System Rack D=380 mm		530x380x2156	45U	2000	2155	530	19"	380	80	165x120x2175	1	24,1	25,6
D=380 mm		530x380x2289	48U	2133	2289	530	19"	380	80	165x120x2310	1	24,7	26,2

*CC= LG for Light Grey RAL 7035 & BL for Black RAL 9005 for customers to define while ordering.

