



TWS-38/10 & TWS-532/10

Designed to be used on shield bond connectors and security screws with an appropriate driver, these sockets are perfect for communication cables, Network Interface Device (NID) mounting and other ground connections.

TWSW-10, TWSW-10SK & TWSW-40

Designed to properly torque security screws with a preset torque, these swivel head torque wrenches are perfect for Network Interface Device (NID) mounting, cable shield bond connectors and other ground connections.

SPECIFICATIONS	TWS-38/10	TWS-532/10	TWSW-10	TWSW-10SK	TWSW-40
HEAD TYPE	6 Point Socket	Hex	Swivel	Swivel	Swivel
SIZE	N/A		3/8" (9.53 mm) Drive Socket	3/8" (9.53 mm) Drive Socket	3/8" (9.53 mm) Drive Socket
TORQUE	N/A	N/A	10 inch-lbs (1.13 N-m)	10 inch-lbs (1.13 N-m)	40 inch-lbs (4.52 N-m)
ROTATION	N/A	N/A	90 degrees	90 degrees	90 degrees
LENGTH	7" (177.8 mm)	N/A	7" (177.8 mm)	7" (177.8 mm)	7" (177.8 mm)
DRIVE SIZE	3/8" (9.53 mm)	3/8" (9.53 mm)	N/A	N/A	N/A
SOCKET SIZE	3/8" (9.53 mm)	5/32" (3.96 mm)	N/A	N/A	N/A
MATERIAL	Chrome Vanadium Steel	Chrome Vanadium Steel	High Carbon Alloy Steel	High Carbon Alloy Steel	High Carbon Alloy Steel
FINISH			Black Oxide	Black Oxide	Black Oxide
HANDLE			Ergonomic Cushion Grip	Ergonomic Cushion Grip	Ergonomic Cushion Grip
COLOR			Red Handle	Red Handle	Blue Handle
WEIGHT	0.607 lbs (0.27 kg)	0.607 lbs (0.27 kg)	0.522 lbs (0.237 kg)	0.602 lbs (0.273 kg)	0.522 lbs (0.237 kg)
UPC #	811490016477	811490019027	811490019041	811490019058	811490012288